



Chain Lube Ceramic True BiO Wet Rides GRiTT by Leatt

Part Number:
Version No: **1.6**
Safety Data Sheet according to Work Health and Safety Regulations (Hazardous Chemicals) 2023 and ADG requirements

Chemwatch Hazard Alert Code: **2**

Initial Date: **27/02/2026**
Revision Date: **18/04/2026**
Print Date: **18/04/2026**
S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Chain Lube Ceramic True BiO Wet Rides GRiTT by Leatt
Synonyms	Not Available
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Grease
--------------------------	--------

Details of the manufacturer or importer of the safety data sheet

Registered company name	Bike Corp.
Address	Moorabin Airport, Victoria Australia 3194, AUSTRALIA
Telephone	+61 3 9518 5400
Fax	Not Available
Website	bikecorp.com.au
Email	sales@bikecorp.com.au

Emergency telephone number

Association / Organisation	Poisons Information Centre
Emergency telephone number(s)	131 126
Other emergency telephone number(s)	Chemwatch 1800 951 288

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability	0	
Toxicity	0	
Body Contact	0	
Reactivity	0	
Chronic	2	

0 = Minimum
1 = Low
2 = Moderate
3 = High
4 = Extreme

Poisons Schedule	Not Applicable
Classification ^[1]	Non hazardous

Label elements

Hazard pictogram(s)	Not Applicable
---------------------	----------------

SIGNAL WORD	NOT APPLICABLE
-------------	----------------

Hazard statement(s)

Not Applicable

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

No further product hazard information.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
122-40-7	< 0.2	alpha-amylcinnamaldehyde
100-52-7	< 0.2	benzaldehyde
123-92-2	0.1	iso-amyl acetate
64742-53-6	< 0.05	naphthenic distillate, light, hydrotreated (severe)
92257-31-3	< 0.03	C.I. Solvent Red 164
128-37-0	< 0.02	2,6-di-tert-butyl-4-methylphenol

Legend: 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: - Wash out immediately with water. - If irritation continues, seek medical attention. - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: - Immediately remove all contaminated clothing, including footwear. - Flush skin and hair with running water (and soap if available). - Seek medical attention in event of irritation.
Inhalation	- If fumes, aerosols or combustion products are inhaled remove from contaminated area. - Other measures are usually unnecessary.
Ingestion	- Immediately give a glass of water. - First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

Advice for firefighters

Fire Fighting	- Alert Fire Brigade and tell them location and nature of hazard. - Wear full body protective clothing with breathing apparatus. - Prevent, by any means available, spillage from entering drains or water course. - Use water delivered as a fine spray to control fire and cool adjacent area. - Avoid spraying water onto liquid pools. DO NOT approach containers suspected to be hot. - Cool fire exposed containers with water spray from a protected location. - If safe to do so, remove containers from path of fire.
Fire/Explosion Hazard	- Combustible. - Slight fire hazard when exposed to heat or flame. - Heating may cause expansion or decomposition leading to violent rupture of containers.

Chain Lube Ceramic True BiO Wet Rides GRITT by Leatt

	- On combustion, may emit toxic fumes of carbon monoxide (CO). - May emit acid smoke. - Mists containing combustible materials may be explosive. Combustion products include: - carbon dioxide (CO2) - other pyrolysis products typical of burning organic material. May emit corrosive fumes. CARE: Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.
HAZCHEM	Not Applicable

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	- Remove all ignition sources. - Clean up all spills immediately. - Avoid breathing vapours and contact with skin and eyes. - Control personal contact with the substance, by using protective equipment. - Contain and absorb spill with sand, earth, inert material or vermiculite. - Wipe up. - Place in a suitable, labelled container for waste disposal.
Major Spills	Moderate hazard. - Clear area of personnel and move upwind. - Alert Fire Brigade and tell them location and nature of hazard. - Wear breathing apparatus plus protective gloves. - Prevent, by any means available, spillage from entering drains or water course. - No smoking, naked lights or ignition sources. - Increase ventilation. - Stop leak if safe to do so. - Contain spill with sand, earth or vermiculite. - Collect recoverable product into labelled containers for recycling. - Absorb remaining product with sand, earth or vermiculite. - Collect solid residues and seal in labelled drums for disposal. - Wash area and prevent runoff into drains. - If contamination of drains or waterways occurs, advise emergency services.

Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	- Avoid skin contact, including inhalation. - Wear protective clothing when risk of exposure occurs. - Use in a well-ventilated area. - Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. - Avoid smoking, naked lights or ignition sources. - Avoid contact with incompatible materials. - When handling, DO NOT eat, drink or smoke. - Keep containers securely sealed when not in use. - Avoid physical damage to containers. - Always wash hands with soap and water after handling. - Work clothes should be laundered separately. - Use good occupational work practice. - Observe manufacturer's storage and handling recommendations contained within this SDS. - Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions. DO NOT allow clothing wet with material to stay in contact with skin
Other information	- Store in original containers. - Keep containers securely sealed. - No smoking, naked lights or ignition sources. - Store in a cool, dry, well-ventilated area. - Store away from incompatible materials and foodstuff containers. - Protect containers against physical damage and check regularly for leaks. - Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container	- Glass container is suitable for laboratory quantities - Metal can or drum - Packaging as recommended by manufacturer. - Check all containers are clearly labelled and free from leaks.
Storage incompatibility	Avoid reaction with oxidising agents



Chain Lube Ceramic True BiO Wet Rides GRITT by Leatt

×

○

+

– Must not be stored together

– May be stored together with specific preventions

– May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)
INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	iso-amyl acetate	Isoamyl acetate	50 ppm / 270 mg/m3	541 mg/m3 / 100 ppm	Not Available	Not Available
Australia Workplace exposure limits for airborne contaminants (WEL list) (Effective from 1 December 2026) - Appendix A - Workplace Exposure Limits	iso-amyl acetate	Amyl acetate (iso-, n-, sec- isomers)	50 ppm / 270 mg/m3	541 mg/m3 / 100 ppm	Not Available	Not Available
Australia Exposure Standards	naphthenic distillate, light, hydrotreated (severe)	Oil mist, refined mineral	5 mg/m3	Not Available	Not Available	Not Available
Australia Workplace exposure limits for airborne contaminants (WEL list) (Effective from 1 December 2026) - Appendix A - Workplace Exposure Limits	2,6-di-tert-butyl-4-methylphenol	2,6-Di-tert-butyl-p-cresol	10 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	2,6-di-tert-butyl-4-methylphenol	2,6-Di-tert-butyl-p-cresol	10 mg/m3	Not Available	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	TEEL-1	TEEL-2	TEEL-3
benzaldehyde	4 ppm	9.9 ppm	59 ppm
iso-amyl acetate	100 ppm	500 ppm	3000* ppm
naphthenic distillate, light, hydrotreated (severe)	1,100 mg/m3	1,800 mg/m3	40,000 mg/m3

OCCUPATIONAL EXPOSURE BANDING

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
alpha-amylcinnamaldehyde	D	> 0.1 to ≤ 1 ppm
benzaldehyde	D	> 0.1 to ≤ 1 ppm
C.I. Solvent Red 164	C	> 0.1 to ≤ 1 milligrams per cubic meter of air (mg/m³)
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

Exposure controls

Appropriate engineering controls	Enclosed local exhaust ventilation is required at points of dust, fume or vapour generation. HEPA terminated local exhaust ventilation should be considered at point of generation of dust, fumes or vapours. Barrier protection or laminar flow cabinets should be considered for laboratory scale handling. A fume hood or vented balance enclosure is recommended for weighing/ transferring quantities exceeding 500 mg. When handling quantities up to 500 gram in either a standard laboratory with general dilution ventilation (e.g. 6-12 air changes per hour) is preferred. Quantities up to 1 kilogram may require a designated laboratory using fume hood, biological safety cabinet, or approved vented enclosures. Quantities exceeding 1 kilogram should be handled in a designated laboratory or containment laboratory using appropriate barrier/ containment technology. Manufacturing and pilot plant operations require barrier/ containment and direct coupling technologies. Barrier/ containment technology and direct coupling (totally enclosed processes that create a barrier between the equipment and the room) typically use double or split butterfly valves and hybrid unidirectional airflow/ local exhaust ventilation solutions (e.g. powder containment booths). Glove bags, isolator glove box systems are optional. HEPA filtration of exhaust from dry product handling areas is required. Fume-hoods and other open-face containment devices are acceptable when face velocities of at least 1 m/s (200 feet/minute) are achieved. Partitions, barriers, and other partial containment technologies are required to prevent migration of the material to uncontrolled areas. For non-routine emergencies maximum local and general exhaust are necessary. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.				
<table><tr><td>Type of Contaminant:</td><td>Air Speed:</td></tr><tr><td>solvent, vapours, etc. evaporating from tank (in still air)</td><td>0.25-0.5 m/s (50-100 f/min.)</td></tr></table>		Type of Contaminant:	Air Speed:	solvent, vapours, etc. evaporating from tank (in still air)	0.25-0.5 m/s (50-100 f/min.)
Type of Contaminant:	Air Speed:				
solvent, vapours, etc. evaporating from tank (in still air)	0.25-0.5 m/s (50-100 f/min.)				

aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2.5 m/s (200-500 f/min.) for extraction of gases discharged 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

The need for respiratory protection should also be assessed where incidental or accidental exposure is anticipated: Dependent on levels of contamination, PAPR, full face air purifying devices with P2 or P3 filters or air supplied respirators should be evaluated.

The following protective devices are recommended where exposures exceed the recommended exposure control guidelines by factors of:

10; high efficiency particulate (HEPA) filters or cartridges

10-25; loose-fitting (Tyvek or helmet type) HEPA powered-air purifying respirator.

25-50; a full face-piece negative pressure respirator with HEPA filters

50-100; tight-fitting, full face-piece HEPA PAPR

100-1000; a hood-shroud HEPA PAPR or full face-piece supplied air respirator operated in pressure demand or other positive pressure mode.

Individual protection measures, such as personal protective equipment



Eye and face protection

When handling very small quantities of the material eye protection may not be required.

For laboratory, larger scale or bulk handling or where regular exposure in an occupational setting occurs:

- Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Face shield. Full face shield may be required for supplementary but never for primary protection of eyes.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

Skin protection

See Hand protection below

Hands/feet protection

NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.

• Contaminated gloves should be replaced.

As defined in ASTM F-739-96 in any application, gloves are rated as:

- Excellent when breakthrough time > 480 min
- Good when breakthrough time > 20 min
- Fair when breakthrough time < 20 min
- Poor when glove material degrades

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

- Rubber gloves (nitrile or low-protein, powder-free latex, latex/ nitrile). Employees allergic to latex gloves should use nitrile gloves in preference.

Chain Lube Ceramic True BiO Wet Rides GRITT by Leatt

	• Double gloving should be considered. • PVC gloves. • Change gloves frequently and when contaminated, punctured or torn. • Wash hands immediately after removing gloves. • Protective shoe covers. [AS/NZS 2210] • Head covering.
Body protection	See Other protection below
Other protection	• For quantities up to 500 grams a laboratory coat may be suitable. • For quantities up to 1 kilogram a disposable laboratory coat or coverall of low permeability is recommended. Coveralls should be buttoned at collar and cuffs. • For quantities over 1 kilogram and manufacturing operations, wear disposable coverall of low permeability and disposable shoe covers. • For manufacturing operations, air-supplied full body suits may be required for the provision of advanced respiratory protection. • Eye wash unit. • Ensure there is ready access to an emergency shower. • For Emergencies: Vinyl suit

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the: **"Forsberg Clothing Performance Index"**.
The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:
Chain Lube Ceramic True BiO Wet Rides GRITT by Leatt

Material	CPI
BUTYL	C
NATURAL RUBBER	C
NEOPRENE	C
NITRILE	C
PE	C
PE/EVAL/PE	C
PVA	C
VITON	C

* CPI - Chemwatch Performance Index
A: Best Selection
B: Satisfactory; may degrade after 4 hours continuous immersion
C: Poor to Dangerous Choice for other than short term immersion
NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -
* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.
Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face
A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Red		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Characteristic	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available

Chain Lube Ceramic True BiO Wet Rides GRITT by Leatt

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	- Unstable in the presence of incompatible materials. - Product is considered stable. - Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

a) Acute Toxicity	Based on available data, the classification criteria are not met.
b) Skin Irritation/Corrosion	Based on available data, the classification criteria are not met.
c) Serious Eye Damage/Irritation	Based on available data, the classification criteria are not met.
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	Based on available data, the classification criteria are not met.
g) Reproductivity	Based on available data, the classification criteria are not met.
h) STOT - Single Exposure	Based on available data, the classification criteria are not met.
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.
j) Aspiration Hazard	Based on available data, the classification criteria are not met.

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Inhalation of oil droplets or aerosols may cause discomfort and may produce chemical inflammation of the lungs.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.

Chain Lube Ceramic True BiO Wet Rides GRITT by Leatt	TOXICITY	IRRITATION
	Not Available	Not Available
alpha-amylicinnamaldehyde	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50: 3730 mg/kg ^[2]	Skin (Human): 1%/2D
		Skin (Rodent - guinea pig): 100mg/24H - Moderate
		Skin (Rodent - guinea pig): 5%/2W - Mild
		Skin (Rodent - rabbit): 100mg/24H - Severe
benzaldehyde		Skin: no adverse effect observed (not irritating) ^[1]
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >1250 mg/kg ^[1]	Eye: adverse effect observed (irritating) ^[1]
	Oral (Mouse) LD50: 28 mg/kg ^[2]	Skin (Rodent - rabbit): 500mg/24H - Moderate
iso-amyl acetate		Skin: adverse effect observed (irritating) ^[1]
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >5000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50: 16600 mg/kg ^[2]	Skin (Rodent - rabbit): 10mg/24H - Mild
naphthenic distillate, light, hydrotreated (severe)		Skin: no adverse effect observed (not irritating) ^[1]
	TOXICITY	IRRITATION

Chain Lube Ceramic True BiO Wet Rides GRITT by Leatt

	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Eye (Rodent - rabbit): 0.1mL
	Inhalation (Rat) LC50: 2.18 mg/l4h ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50: >5000 mg/kg ^[2]	Skin (Rodent - rabbit): 0.5mL/24H - Moderate
		Skin (Rodent - rabbit): 500mg - Severe
		Skin: no adverse effect observed (not irritating) ^[1]
C.I. Solvent Red 164	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >10200 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50: >5000 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
2,6-di-tert-butyl-4-methylphenol	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye (Rodent - rabbit): 100mg/24H - Moderate
	Oral (Rat) LD50: 890 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
		Skin (Human): 500mg/48H - Mild
		Skin (Rodent - rabbit): 500mg/48H - Moderate
		Skin: no adverse effect observed (not irritating) ^[1]

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

naphthenic distillate, light, hydrotreated (severe)	The materials included in the Lubricating Base Oils category are related from both process and physical-chemical perspectives; The potential toxicity of a specific distillate base oil is inversely related to the severity or extent of processing the oil has undergone, since: • The adverse effects of these materials are associated with undesirable components, and • The levels of the undesirable components are inversely related to the degree of processing; • Distillate base oils receiving the same degree or extent of processing will have similar toxicities; • The potential toxicity of residual base oils is independent of the degree of processing the oil receives. • The reproductive and developmental toxicity of the distillate base oils is inversely related to the degree of processing. Unrefined & mildly refined distillate base oils contain the highest levels of undesirable components, have the largest variation of hydrocarbon molecules and have shown the highest potential cancer-causing and mutation-causing activities. Highly and severely refined distillate base oils are produced from unrefined and mildly refined oils by removing or transforming undesirable components. In comparison to unrefined and mildly refined base oils, the highly and severely refined distillate base oils have a smaller range of hydrocarbon molecules and have demonstrated very low mammalian toxicity. Testing of residual oils for mutation-causing and cancer-causing potential has shown negative results, supporting the belief that these materials lack biologically active components or the components are largely non-bioavailable due to their molecular size. Toxicity testing has consistently shown that lubricating base oils have low acute toxicities. Numerous tests have shown that a lubricating base oil s mutagenic and carcinogenic potential correlates with its 3-7 ring polycyclic aromatic compound (PAC) content, and the level of DMSO extractables (e.g. IP346 assay), both characteristics that are directly related to the degree/conditions of processing.
alpha-amylcinnamaldehyde	Animal testing suggests that the toxicity through swallowing cinnamyl aldehyde derivatives is very low. The potential for toxicity through skin exposure is similarly low. Cinnamaldehyde and its alkyl-substituted derivatives do not directly cause mutations or genetic damage. However, animal testing suggests that they may result in poor development of the skull and kidney in the foetus. The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration. These substances are generally regarded as safe. Cinnamyl derivatives are natural components of certain foods, and are found in greater amounts there than in flavouring substances. They are rapidly absorbed, broken down and eliminated in the human body, and do not have significant potential to cause genetic toxicity and mutations.
benzaldehyde	Somnolence , tremor, coma, ulceration of the small intestine, increased urine volume recorded. For certain benzyl derivatives: The members of this group are rapidly absorbed through the gastrointestinal tract, metabolised primarily in the liver, and excreted primarily in the urine either unchanged or as conjugates of benzoic acid derivatives. At high dose levels, gut micro-organisms may act to produce minor amounts of breakdown products. However, no adverse effects have been reported even at repeated high doses. Similarly, no effects were observed on reproduction, foetal development and tumour potential. This is a member or analogue of a group of benzyl derivatives generally regarded as safe (GRAS), based partly on their self-limiting properties as flavouring substances in food. In humans and other animals, they are rapidly absorbed, broken down and excreted, with a wide safety margin. They also lack significant potential to cause genetic toxicity and mutations. The intake of benzyl derivatives as natural components of traditional foods is actually higher than the intake as intentionally added flavouring substances.
2,6-di-tert-butyl-4-methylphenol	* Degussa SDS Effects such as behavioral changes, reduction in body weight gain, and decrement in body weight have been observed after long-term administration of BHT to mice and rats. Toxic effects may be attributed more to BHT metabolites than to their parent compound, only a few studies have focused on their carcinogenicity and toxicity, and not only on that of BHT. The metabolite BHT-QM (syn: 2,6-di-tert-butyl-1,4-methylene-2,5-cyclohexadien-1-one, CAS RN: 2607-52-5) is a very reactive compound which is considered to play a significant role in hepatotoxicity, pneumotoxicity, and skin tumor promotion in mice. In addition, it was reported that another quinone derivative, BHT-OH(t)QM (syn 2-tert-butyl-6-(2-hydroxy-tert-butyl-4-methylene-2,5-cyclohexadien-1-one, CAS RN: 124755-19-7), is chemically more reactive than BHT-QM, and it has been recognized as the principal metabolite responsible for lung tumor promotion activity of BHT in mice. BHT has been reported to exert prooxidant effects under certain conditions. Thus, when BHT was added in excess to a wheat seedling medium in aerobic conditions, an enhancement of the generation rate of superoxide anion was observed. This is a reactive particle that may damage cellular structures at high concentrations In addition, an increase in hepatic microsomal lipid peroxidation was observed in rats fed with diets containing 0.2% of BHT for 30 days. Due to this ability of BHT to exert prooxidant effects at high concentrations, it has been used to induce experimental models of oxidative stress in several animals and fungi in order to study the protective effects of other compounds. Quinone methide derivatives form adducts with several proteins, including enzymes that protect cells from oxidative stress; this prooxidant state can also lead to cell oxidative damage. It must be noted that relationships between chronic oxidative stress and tumor promotion are well known Some authors have reported that at high aeration rate, BHT can react with molecular oxygen rather than with the reactive oxygen species present, yielding BHT-phenoxy radical and superoxide anion. In addition, the phenolic radical itself may undergo redox recycling which can be a critical factor depending on the reductant involved However, it has to be noted that BHT-phenoxy radical has been reported to be relatively stable. Furthermore, the potential reactivity of BHT-derived metabolites should be taken into account; some studies reported that not only BHT but also its metabolites, such as BHT-Q and BHT-QM, can act as prooxidant. As BHT undergoes several reactions during biotransformation, a large number of intermediate metabolites have been identified. However, their nature and concentration depend on the

Chain Lube Ceramic True BiO Wet Rides GRITT by Leatt

environmental conditions and on the animal species. Although the changes undergone by BHT during in vivo digestion processes have not been studied, after submission of a fluid deep-frying fat containing BHT and BHT-QM to an in vitro gastrointestinal digestion model, both these were detected in the digested samples. These results indicate that BHT and its toxic metabolite could remain bioaccessible for intestinal absorption. Studies concerning BHT metabolism have shown that, unlike other synthetic antioxidants, BHT is a potent inducer of the microsomal monooxygenase system and its major route of degradation is oxidation catalyzed by cytochrome . Studies have reported potential toxicity derived from the ingestion or administration of BHT. As for acute oral toxicity, although this is considered low in animals, it must be noted that 2 clinical cases were reported in patients who suffered acute neurotoxicity and gastritis after ingesting a high dose of BHT (4 and 80 g without medical prescription) to cure recurrent genital herpes. Regarding short-term subchronic toxicity studies, it has been reported that BHT causes dose-related increase in the incidence and severity of toxic nephrosis in mice, nephrotoxicity and pneumotoxicity in rats, and in chicken a marked congestion of the liver and kidney, as well as diffuse enlargement of the liver with rounded borders and rupture with hemorrhaging . It has to be noted that the EFSA Panel (2012) pointed out certain inconsistencies in the findings obtained from the short-term and subchronic toxicity studies. Several genotoxicity studies on BHT concluded that BHT does not represent a genotoxic risk, because most of the studies carried out to that date had shown BHT was not able to induce mutations or to damage deoxyribonucleic acid (DNA). Nevertheless, it must be mentioned that other studies reported contrary results. The effect of BHT and 7 of its metabolites on in vitro DNA cleavage was studied and the metabolites BHT-Q (syn: 2,6-di-tert-butyl-2,5-cyclohexadiene-1,4-dione, CAS RN: 719-22-2), BHT-CHO (syn: 3,5-di-tert-butyl-4-hydroxybenzaldehyde, CAS RN: 1620-98-0 and BHT-OOH (syn: 2,6-di-tert-butyl-4-methyl-4-hydroperoxy-2,5-cyclohexadien-1-one, CAS RN: 6485-57-0) were able to cleave DNA.. The Panel on Food Additives and Nutrient Sources Added to Food of the European Food Safety Authority (EFSA) recognized that these positive genotoxicity results may be due to the prooxidative chemistry of BHT, which gives rise to reactive metabolites. Some studies addressed the carcinogenicity and chronic toxicity of BHT and its metabolites in rodents with contradictory results. Thus, mice-fed dietary BHT for a year developed marked hyperplasia of the hepatic bile ducts with an associated subacute cholangitis. Moreover, after 104 wk of administration of BHT, the formation of hepatocellular tumors in male mice was observed. After 10 months of feeding mice with a diet containing different amounts of BHT, an increased incidence of liver tumors in male, but not female, animals was also reported . However, in a similar study no evidence of the carcinogenicity of BHT administered to mice was observed. Studies performed in rats also reported dose-related increases in hepatocellular adenomas and carcinomas; nevertheless, other studies carried out with rats showed no consistent carcinogenic effects. Several studies have demonstrated the potential of BHT to act either as a tumor promotor or as a tumor suppressor, modulating the carcinogenicity of some well-known carcinogens. Barbara Nieva-Echevarria et al: Comprehensive reviews in Food Science and Food Safety, Vol 14, Dec 2014 <https://onlinelibrary.wiley.com/doi/10.1111/1541-4337.12121/pdf>

Laboratory (in vitro) and animal studies show, exposure to the material may result in a possible risk of irreversible effects, with the possibility of producing mutation.

for bridged alkyl phenols:

Acute toxicity: Acute oral and dermal toxicity data are available for all but two of the substances in the group. The data show that acute toxicity of these substances is low. The testing for acute toxicity spans five decades

Repeat dose toxicity: Repeat dose studies on the members of this category include both subchronic and chronic exposures. The liver is identified as the target organ in rats for all of the substances tested. NOAEL s or NOEL s in rats for 13- week studies ranged from 100 ppm (approximately 5 mg/kg/day) to 500 ppm (approximately 25 mg/kg/day) while NOAEL s or NOEL s in rats for chronic studies were the same, 25 mg/kg/day (500 ppm).

Reproductive toxicity: Evaluation of effects on reproduction for the bridged alkyl phenols is supplemented by histopathological data on male and female reproductive organs in repeated dose studies. The data on the effects of bridged alkyl phenols on reproduction and reproductive organs span the range of structures and molecular weights. While not all of the data for reproductive effects are from reproduction studies, microscopic evaluations of reproductive organs along with other short-term tests for reproductive effects provide adequate data to evaluate the effects of these bridged alkyl phenols on reproduction. It can be concluded that reproductive toxicity is low. Typically a two-year chronic feeding study provides data for 4,4'-thiobis-6-(t-butyl-m-cresol) (96-69-5). No adverse effects were noted on reproductive organs

Genotoxicity: Data from bacterial reverse mutation assays and in vitro and in vivo chromosome aberration studies were reviewed. Adequate bacterial gene mutation assays have been conducted with all of the category chemicals except two. Chromosome aberration studies, in vitro and/or in vivo, are available for all but two substances. The mutagenicity data span the range of structures and molecular weights and data can be bridged from other members of the group to meet any outstanding requirements. The weight of evidence for mutagenic potential for this category indicates these substances are not mutagenic.

Carcinogenicity: The mutagenicity data combined with the animal data plus the long historical use of BHT (128-37-0) indicate that the chemicals in this class are not expected to exhibit any significant potential to cause cancer. The weight of the evidence indicates that these chemicals are not genotoxic.

The Bridged Alkyl Phenols Category consists of a group of chemicals in which two molecules of mono or di-substituted alkyl (C1, C4, and/or C9) phenols are "bridged" or linked by a single atom (carbon or sulfur). The carbon atom linking the alkyl phenol groups contains hydrogen, propyl, or methyl substitutions. CAS No. 128-37-0 (BHT) is included in this category for data purposes because it is an alkyl phenol with a single carbon group such as the ones that link the phenol groups

Data show that acute toxicity following oral and topical use of hindered phenols is low. They are not proven to cause mutations. However, long term use may affect the liver, thyroid, kidney and lymph nodes. Liver tumours have been reported.

Chain Lube Ceramic True BiO Wet Rides GRITT by Leatt & 2,6-di-tert-butyl-4-methylphenol	ferroptosis inhibitors are currently being treated systemically rather than specifically, which may have multiple side effects. For example, Desferoxamin (DFO), an iron chelating agent, is known to have a short half-life, need long-term subcutaneous infusions, and provoke ototoxicity and neurotoxicity. Deferasirox (DFX), an iron chelator, is associated with gastrointestinal and renal toxicity .
Chain Lube Ceramic True BiO Wet Rides GRITT by Leatt & naphthenic distillate, light, hydrotreated (severe)	For highly and severely refined distillate base oils: In animal studies, the acute, oral, semilethal dose is >5g/kg body weight and the semilethal dose by skin contact is >2g/kg body weight. The semilethal concentration for inhalation is 2.18 to >4 mg/L. The materials have varied from "non-irritating" to "moderately irritating" when tested for skin and eye irritation. Testing for sensitisation has been negative. The effects of repeated exposure vary by species; in animals, effects to the testes and lung have been observed, as well as the formation of granulomas. In animals, these substances have not been found to cause reproductive toxicity or significant increases in birth defects. They are also not considered to cause cancer, mutations or chromosome aberrations.
benzaldehyde & 2,6-di-tert-butyl-4-methylphenol	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.
naphthenic distillate, light, hydrotreated (severe) & 2,6-di-tert-butyl-4-methylphenol	The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.
C.I. Solvent Red 164	No significant acute toxicological data identified in literature search.
Chain Lube Ceramic True BiO Wet Rides GRITT by Leatt & alpha-amylcinnamaldehyde & benzaldehyde & 2,6-di-tert-butyl-4-methylphenol	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.
alpha-amylcinnamaldehyde & benzaldehyde & 2,6-di-tert-butyl-4-methylphenol	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis

Chain Lube Ceramic True BiO Wet Rides GRITT by Leatt

	is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.
Chain Lube Ceramic True BiO Wet Rides GRITT by Leatt & alpha-amylcinnamaldehyde & benzaldehyde	Adverse reactions to fragrances in perfumes and fragranced cosmetic products include allergic contact dermatitis, irritant contact dermatitis, sensitivity to light, immediate contact reactions, and pigmented contact dermatitis. Airborne and connubial contact dermatitis occurs. Contact allergy is a lifelong condition, so symptoms may occur on re-exposure. Allergic contact dermatitis can be severe and widespread, with significant impairment of quality of life and potential consequences for fitness for work. If the perfume contains a sensitizing component, intolerance to perfumes by inhalation may occur. Symptoms may include general unwellness, coughing, phlegm, wheezing, chest tightness, headache, shortness of breath with exertion, acute respiratory illness, hayfever, asthma and other respiratory diseases. Perfumes can induce excess reactivity of the airway without producing allergy or airway obstruction. Breathing through a carbon filter mask had no protective effect. Occupational asthma caused by perfume substances, such as isoamyl acetate, limonene, cinnamaldehyde and benzaldehyde, tend to give persistent symptoms, even though the exposure is below occupational exposure limits. Prevention of contact sensitization to fragrances is an important objective of public health risk management. Hands: Contact sensitization may be the primary cause of hand eczema or a complication of irritant or atopic hand eczema. However hand eczema is a disease involving many factors, and the clinical significance of fragrance contact allergy in severe, chronic hand eczema may not be clear. Underarm: Skin inflammation of the armpits may be caused by perfume in deodorants and, if the reaction is severe, it may spread down the arms and to other areas of the body. In individuals who consulted a skin specialist, a history of such first-time symptoms was significantly related to the later diagnosis of perfume allergy. Face: An important manifestation of fragrance allergy from the use of cosmetic products is eczema of the face. In men, after-shave products can cause eczema around the beard area and the adjacent part of the neck. Men using wet shaving as opposed to dry have been shown to have an increased risk of allergic to fragrances. Irritant reactions: Some individual fragrance ingredients, such as citral, are known to be irritant. Fragrances may cause a dose-related contact urticaria (hives) which is not allergic; cinnamal, cinnamic alcohol and Myroxylon pereirae are known to cause hives, but others, including menthol, vanillin and benzaldehyde have also been reported. Pigmentary anomalies: Type IV allergy is responsible for "pigmented cosmetic dermatitis", referring to increased pigmentation on the face and neck. Testing showed a number of fragrance ingredients were associated, including jasmine absolute, ylang-ylang oil, cananga oil, benzyl salicylate, hydroxycitronellal, sandalwood oil, geraniol and geranium oil. Light reactions: Musk ambrette produced a number of allergic reactions mediated by light and was later banned from use in Europe. Furocoumarins (psoralens) in some plant-derived fragrances have caused phototoxic reactions, with redness. There are now limits for the amount of furocoumarins in fragrances. Phototoxic reactions still occur, but are rare. General/respiratory: Fragrances are volatile, and therefore, in addition to skin exposure, a perfume also exposes the eyes and the nose / airway. It is estimated that 2-4% of the adult population is affected by respiratory or eye symptoms by such an exposure. It is known that exposure to fragrances may exacerbate pre-existing asthma. Asthma-like symptoms can be provoked by sensory mechanisms. A significant association was found between respiratory complaints related to fragrances and contact allergy to fragrance ingredients and hand eczema. Fragrance allergens act as haptens, low molecular weight chemicals that cause an immune response only when attached to a carrier protein. However, not all sensitizing fragrance chemicals are directly reactive, but require previous activation. A prohaptens is a chemical that itself causes little or no sensitization, but is transformed into a hapten in the skin (bioactivation), usually via enzyme catalysis. It is not always possible to know whether a particular allergen that is not directly reactive acts as a prehaptens or a prohaptens , or both. Prohaptens: Compounds that are bioactivated in the skin and thereby form haptens are referred to prohaptens. The possibility of a prohaptens being activated cannot be avoided by outside measures. Activation processes increase the risk for cross-reactivity between fragrance substances. Various enzymes play roles in both activating and deactivating prohaptens. Skin-sensitizing prohaptens can be recognized and grouped into chemical classes based on knowledge of xenobiotic bioactivation reactions, clinical observations and/or studies of sensitization. QSAR prediction: Prediction of sensitization activity of these substances is complex, especially for those substances that can act both as pre- and prohaptens.

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend: × – Data either not available or does not fill the criteria for classification
 ✓ – Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity					
Chain Lube Ceramic True BiO Wet Rides GRITT by Leatt	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
alpha-amylcinnamaldehyde	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	EC50	72h	Algae or other aquatic plants	1.18mg/l	2
	EC50	48h	Crustacea	0.28mg/l	2
	NOEC(ECx)	504h	Crustacea	0.041mg/l	2
	EC50	96h	Algae or other aquatic plants	1.715mg/l	2
	LC50	96h	Fish	0.91mg/l	2
benzaldehyde	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	EC50	72h	Algae or other aquatic plants	0.028mg/L	4
	EC50	48h	Crustacea	19.7mg/l	2
	EC10(ECx)	72h	Algae or other aquatic plants	0.021mg/l	2
	EC50	96h	Algae or other aquatic plants	23.065mg/l	2
	LC50	96h	Fish	0.8-1.44mg/L	4
	ErC50	72h	Algae or other aquatic plants	33.1mg/l	2

Chain Lube Ceramic True BiO Wet Rides GRITT by Leatt

iso-amyl acetate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	EC50	72h	Algae or other aquatic plants	156mg/l	2
	EC50	48h	Crustacea	26.3mg/l	2
	NOEC(ECx)	48h	Crustacea	3.77mg/l	2
	EC50	96h	Algae or other aquatic plants	235mg/l	2
naphthenic distillate, light, hydrotreated (severe)	LC50	96h	Fish	11.1mg/l	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	ErC50	72h	Algae or other aquatic plants	>1000mg/l	1
	EC50	48h	Crustacea	>1000mg/l	1
	EC50	96h	Algae or other aquatic plants	>1000mg/l	1
C.I. Solvent Red 164	NOEC(ECx)	504h	Crustacea	>1mg/l	1
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not ENDPOINT	TEST DURATION (HR)	SPECIES	Not VALUE	Not SOURCE
2,6-di-tert-butyl-4-methylphenol	BCF	1344h	Fish	220-2800	7
	EC50	72h	Algae or other aquatic plants	>0.42mg/l	1
	EC50	48h	Crustacea	>0.17mg/l	2
	EC0(ECx)	48h	Crustacea	>=0.31mg/l	1
	EC50	96h	Algae or other aquatic plants	0.758mg/l	2
	LC50	96h	Fish	0.199mg/l	2
	ErC50	72h	Algae or other aquatic plants	>0.42mg/l	1
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE

Legend: *Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data*

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.
Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
alpha-amylcinnamaldehyde	LOW	LOW
benzaldehyde	LOW	LOW
iso-amyl acetate	LOW	LOW
2,6-di-tert-butyl-4-methylphenol	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
alpha-amylcinnamaldehyde	HIGH (LogKOW = 4.7)
benzaldehyde	LOW (LogKOW = 1.48)
iso-amyl acetate	LOW (LogKOW = 2.25)
2,6-di-tert-butyl-4-methylphenol	HIGH (BCF = 2500)

Mobility in soil

Ingredient	Mobility
alpha-amylcinnamaldehyde	LOW (KOC = 2182)
benzaldehyde	LOW (KOC = 32.67)
iso-amyl acetate	LOW (KOC = 32.24)
2,6-di-tert-butyl-4-methylphenol	LOW (KOC = 23030)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Chain Lube Ceramic True BiO Wet Rides GRITT by Leatt

Product / Packaging disposal

- Containers may still present a chemical hazard/ danger when empty.
 - Return to supplier for reuse/ recycling if possible.
- Otherwise:
- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
 - Where possible retain label warnings and SDS and observe all notices pertaining to the product.
- Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.
- A Hierarchy of Controls seems to be common - the user should investigate:
- Reduction
 - Reuse
 - Recycling
 - Disposal (if all else fails)
- This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.
- **DO NOT allow wash water from cleaning or process equipment to enter drains.**
 - It may be necessary to collect all wash water for treatment before disposal.
 - In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
 - Where in doubt contact the responsible authority.
 - Recycle wherever possible or consult manufacturer for recycling options.
 - Consult State Land Waste Authority for disposal.
 - Bury or incinerate residue at an approved site.
 - Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
alpha-amylcinnamaldehyde	Not Applicable
benzaldehyde	Not Applicable
iso-amyl acetate	Not Applicable
naphthenic distillate, light, hydr otreated (severe)	Not Applicable
C.I. Solvent Red 164	Not Applicable
2,6-di-tert-butyl-4-methylphenol	Not Applicable

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
alpha-amylcinnamaldehyde	Not Applicable
benzaldehyde	Not Applicable
iso-amyl acetate	Not Applicable
naphthenic distillate, light, hydr otreated (severe)	Not Applicable
C.I. Solvent Red 164	Not Applicable
2,6-di-tert-butyl-4-methylphenol	Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

ALPHA-AMYL CINNAMALDEHYDE IS FOUND ON THE FOLLOWING REGULATORY LISTS

- Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

- Australian Inventory of Industrial Chemicals (AIIC)

BENZALDEHYDE IS FOUND ON THE FOLLOWING REGULATORY LISTS

- Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
- Australian Inventory of Industrial Chemicals (AIIC)

ISO-AMYL ACETATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

- Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
- Australian Inventory of Industrial Chemicals (AIIC)

NAPHTHENIC DISTILLATE, LIGHT, HYDROTREATED (SEVERE) IS FOUND ON THE FOLLOWING REGULATORY LISTS

- Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
- Australian Inventory of Industrial Chemicals (AIIC)
- Chemical Footprint Project - Chemicals of High Concern List

C.I. SOLVENT RED 164 IS FOUND ON THE FOLLOWING REGULATORY LISTS

- Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
- Australian Inventory of Industrial Chemicals (AIIC)
- International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

2,6-DI-TERT-BUTYL-4-METHYLPHENOL IS FOUND ON THE FOLLOWING REGULATORY LISTS

- Australian Inventory of Industrial Chemicals (AIIC)
- International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)
- International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

Additional Regulatory Information

Not Applicable

Additional State Regulatory Information

Not Available

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (alpha-amylcinnamaldehyde, benzaldehyde, iso-amyl acetate, naphthenic distillate, light, hydrotreated (severe), C.I. Solvent Red 164)
China - IECSC	Yes
Columbia - Columbia National Industrial Chemicals Inventory	No (alpha-amylcinnamaldehyde, benzaldehyde, iso-amyl acetate, naphthenic distillate, light, hydrotreated (severe), C.I. Solvent Red 164, 2,6-di-tert-butyl-4-methylphenol)
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	No (alpha-amylcinnamaldehyde, naphthenic distillate, light, hydrotreated (severe), C.I. Solvent Red 164)
Vietnam - NCI	Yes
Russia - FBEPH	No (C.I. Solvent Red 164)
UAE - Control List (Banned/Restricted Substances)	No (alpha-amylcinnamaldehyde, benzaldehyde, iso-amyl acetate, naphthenic distillate, light, hydrotreated (severe), C.I. Solvent Red 164, 2,6-di-tert-butyl-4-methylphenol)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 OTHER INFORMATION

Revision Date	18/04/2026
Initial Date	27/02/2026

Other information

Ingredients with multiple cas numbers

Name	CAS No
C.I. Solvent Red 164	71819-51-7, 92257-31-3
2,6-di-tert-butyl-4-methylphenol	128-37-0, 31194-40-8, 97123-41-6, 25377-21-3, 102962-45-8, 259752-53-9, 290348-23-1, 36631-28-4, 42615-30-5, 50356-19-9, 50641-99-1, 52683-46-2, 53571-70-3, 58500-82-6, 83047-16-9, 86819-59-2, 64502-99-4

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- PC - TWA: Permissible Concentration-Time Weighted Average
- PC - STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit,
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- MARPOL: International Convention for the Prevention of Pollution from Ships
- IMSBC: International Maritime Solid Bulk Cargoes Code
- IGC: International Gas Carrier Code
- IBC: International Bulk Chemical Code
- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.