DATE: 19-1-2017

## **TOURING TRAILER - PTT**

# PACIFIC





### Bicycle Cargo Trailer

#### Owner's Manual & Instruction

You should not use the Carrier if you have not read and understood the contents of this Owner's Manual. Failure to heed this warning may result in serious or fatal injury.

The bicycle follower can be coupled to bicycles to me to the bicycle size of 20 " to 28".

- Our bicycle followers are determined only for the transport of luggage, no children or animals may be transported.
- Maximum useful load 27 kg
- As with an automobile is valid: The higher the useful load of the follower, the greater is the effect on the Handling and braking distance of the vehicle.
- The luggage must be certainly fastened.
- Before every journey you check your bicycle brake for the functionality.
- Maximum speed 40 KM/H think by the bending always of the fact that now your bicycle has become longer about 140 cm.
- Please, check whether the bicycle is likely to pull the bicycle follower. Ask your bicycle trader or read the instructions for use of the bicycle manufacturer

Step 1: Install mudguard(4) on wheel fork(3) as per below images:













Step 2: Install wheel(5) by quick release as per below images:








Step 3: Connect loading frame(1) and the fork with wheel by connect nut(10) as per below images:



Step 4: Install the damper(6) on the loading frame(1) as per below images:



#### Step 5:



turn off front fork revolver and take out the connect spindle



the parts



combine the trailer frame and front fort, put in connect spindle and fix



put in the safe flag, the trailer assembling finished.

#### THE BIKE NOT USING THE QUICK RELEASE



(include) (optional) different bike adapter to the different bike





tight the screw



put assembled trailer on the quick release



put down the safe lock and move down along the arrow sign



now it is locked



put the bag on the trailer correctly.

